


DC-1338i

10.0 MegaPixel

- ▶ 10.0 MegaPixel CCD sensor
- ▶ 3x optical zoom, 4x digital zoom
- ▶ 3.0" TFT-LCD (230K), 960 x 240 dots
- ▶ 21 scene modes
- ▶ Lithium-ion rechargeable battery

Highlights

- ▶ Digital photo stabilizer
- ▶ Face Tracking
- ▶ ISO 1600
- ▶ SDHC compatible (4 GB)
- ▶ AF lamp
- ▶ Histogram
- ▶ Metal body



DC-1338i

Technical details

| | |
|-----------------------|--------------------|
| ▶ Image sensor | |
| Sensor | 10.0 MegaPixel CCD |

| | |
|---------------------------|--|
| ▶ Optics | |
| Lens and type | 6 elements in 5 groups, (incl. 3 pcs aspherical lenses) |
| Focal length | f = 7.4 (W) ~ 22.2 (T) mm |
| Equivalent to 35mm camera | 35.1 (W) ~ 105.3 (T) mm |
| Brightness | F/2.8 (W), F/5.1 (T) |
| Shutter speed | 1/2000 ~ 8 sec. |

| | |
|---------------|----|
| ▶ Zoom | |
| Digital zoom | 4x |
| Optical zoom | 3x |

| | |
|-------------------|--|
| ▶ Focusing | |
| Focus range | T: 50 cm ~ Infinity, W: 10 cm ~ Infinity |

| | |
|-----------------------|---|
| ▶ Exposure | |
| Exposure compensation | -2EV to +2EV in 1/3 step, (-2.0, -1.7, -1.3, -1.0, -0.7, -0.3, 0.0, +0.3, +0.7, +1.0, +1.3, +1.7, +2.0) |
| Exposure meter | Center-weighted, multi, spot |
| ISO | Auto, 50, 100, 200, 400, 800, 1600 |
| White balance | Daylight, cloudy, tungsten, fluorescent_H, fluorescent_L, customer |
| Exposure control | Automatic/manual |

| | |
|----------------|--|
| ▶ LCD | |
| Colour display | 3.0" TFT-LCD (230K), 960 x 240 dots |

| | |
|-----------------|------------------------------|
| ▶ Memory | |
| Memory internal | 16 MB |
| Memory external | 2GB (SD-card) and 4GB (SDHC) |

| | |
|---------------------|--|
| ▶ Resolution | |
| Still image | 3584 x 2688 (default), 3648 x 2432 (3:2), 3584 x 2016 (16:9), 3328 x 2496, 2560 x 1920, 2048 x 1536, 640 x 480 |
| Video | 848 x 480 (16:9), 640 x 480, 320 x 240, 160 x 128, 30 fps |

| | |
|----------------------|---|
| ▶ File format | |
| Still image | JPEG, EXIF 2.2, support DPOF, PictBridge compatible |
| Video | AVI |
| Audio | WAV |

| | |
|---------------------|---|
| ▶ Scene mode | |
| Scene mode | Backlight, building, candle, fireworks, food, kids, landscape, movie, night scene, night scene portrait, party, portrait, program, Q mode, snow, soft flowing water, soft skin, sports, sunset, text, voice REC |

| | |
|---------------------|---|
| ▶ Flash mode | |
| Flash light | Auto, red-eye reduction, slow sync., forced On, Off |

| | |
|--------------------|----------|
| ▶ Interface | |
| USB | 2.0 |
| TV out | PAL/NTSC |

| | |
|-----------------------|----------------------------------|
| ▶ Power source | |
| Power supply | Lithium-ion rechargeable battery |
| Auto power off | Off, 1 min., 3 min., 5 min. |

| | |
|-------------------|---|
| ▶ Others | |
| Camera dimensions | approx. 94 x 20 x 56 mm (W x H x L) |
| Body | Metal |
| Weight | 139 g (w/o battery) |
| Menu language | English, German, Spanish, French, Italian, Portuguese, Dutch, Swedish, Greek, Czech, Polish, Turkish, Hungarian, Russian, Arabic, Romanian, Thai, Japanese, Simple Chinese, Korean, Traditional Chinese |

| | |
|----------------------|--|
| ▶ Accessories | |
| | USB cable, AV cable, Lithium-ion battery, battery charger & adaptor, hand strap, pouch, CD-Rom |

| | |
|---------------------|----------------------------------|
| ▶ Logistics | |
| Item number | 06850 |
| Bar code | 4004781068507 |
| Packaging size | 8,7 x 16,1 x 22,5 cm (W x H x L) |
| Packaging unit | 5 |
| Weight | approx. 832 g |
| Weight (boxed unit) | approx. 4,8 |
| Dimensions ship box | 25 x 19 x 46 cm (W x H x L) |

Dealer stamp

AGFAPHOTO is used under license of Agfa-Gevaert NV&Co. KG. Agfa-Gevaert NV&Co. KG does not manufacture this product or provide any product warranty or support. For service, support and warranty information, contact the distributor or manufacturer. All other brands and product names are registered trademarks of their respective owners. Product design and technical features can be changed without notice.